

# BNC CONNECTORS



## TERMINATORS

• All Terminators has power rating of 0.5 Watt

### Plugs

<b>BNC-3061</b>	50 Ω
<b>BNC-3061-1</b>	50 Ω, 1%
<b>BNC-3061-2</b>	50 Ω, 1%, W/Chain, Green Cap
<b>BNC-7861</b>	50 Ω, 1 %, Die Casted
<b>BNC-3062</b>	75 Ω
<b>BNC-3062-1</b>	75 Ω, 1%
<b>BNC-3062-2</b>	75 Ω, 1%, W/Chain, Purple Cap
<b>BNC-7862</b>	75 Ω, 1 %, Die Casted
<b>BNC-3063</b>	93 Ω
<b>BNC-3063-1</b>	93 Ω, 1%
<b>BNC-3063-2</b>	93 Ω, 1%, W/Chain, White Cap
<b>BNC-7863</b>	93 Ω, 1 %, Die Casted
<b>BNC-3061-BULK</b>	100/PACK

### Jacks

<b>BNC-7864</b>	50 Ω
<b>BNC-7865</b>	75 Ω
<b>BNC-7866</b>	93 Ω

• All Jacks are 1%, Die Casted



**BNC-7864**



**BNC-3061-2**

## 75 Ohm SERIES

<b>BNC-3021-75</b>	For RG-59/U, 62/U PVC
<b>BNC-3021-7511</b>	RG-59/U, 62/U, 1.1 mm Pin
<b>BNC-3023-75</b>	RG-6/U, 3pc Crimp Plug
<b>BNC-3024-75</b>	RG-59/U Teflon, 3pc Crip
<b>BNC-3026-75</b>	For Belden 8281, 3pc Crip
<b>BNC-3027-75</b>	For Belden 8218, 3pc Crip
<b>BNC-3029-11</b>	RG-11, 3pc Crimp Plug, 75Ω
<b>BNC-3029-179-75</b>	For RG-179/U, Dual Crimp Type
<b>BNC-3029-735A-75</b>	For 735A, Dual Crimp Type
<b>BNC-3062</b>	Terminator, Male, 0.5W
<b>BNC-3062-1</b>	Terminator, Male, 0.5W, 1%
<b>BNC-3062-2</b>	Terminator, Male, W/chain, 0.5W, 1%
<b>BNC-3071-75</b>	RG-59, 75Ω
<b>BNC-3073-75</b>	RG-6, 75 Ω
<b>BNC-3074-75</b>	RG-59/U, Plenum
<b>BNC-3121-75</b>	RG-59/U, 62/U
<b>BNC-3121-7511</b>	RG-59, 62
<b>BNC-3123-75</b>	RG-56
<b>BNC-3127-75</b>	For Belden 8218
<b>BNC-3129-179-75</b>	RG-179/U
<b>BNC-3192-75</b>	UG-492D/U, Chassis Mount
<b>BNC-3193-75</b>	Isolated UG-492D/U, Chassis Mount
<b>BNC-3194-75</b>	Recep. Solder Type, Chas. Mnt.UG-1094D/U
<b>BNC-3306-75</b>	M-F Right Angle
<b>BNC-3314-75</b>	UG-914/U, F-F, Female Inline Splice
<b>BNC-3374-75</b>	"T" Adaptor, J-P-J, UG-274D/U
<b>BNC-7029-179-75</b>	RG-179/U, Dual Crimp Type
<b>BNC-7071-75</b>	RG-59, 75Ω
<b>BNC-7073-75</b>	RG-6, 75Ω
<b>BNC-7862</b>	Terminator Plug, 75Ω, 1 %, Die Casted
<b>BNC-7865</b>	Terminator Jack, 75Ω, 1% & 1/2W



See PG 64 for Connector-Tool Reference

## SNAP FIT

<b>BNC-7071SN</b>	For RG-59 Tri-Shield
<b>BNC-7073SN</b>	For RG-6 Tri-Shield
<b>BNC-7074SN</b>	For RG-59 Quad-Shield
<b>BNC-7079SN</b>	For RG-6 Quad-Shield



See PG 61 for Crimp Tool

## DUST CAPS

For Jacks

**BNC-DSTCP-P**

For Plugs

**BNC-DSTCP-S**



## FERRULES, PIN, BUSHING

<b>FER-6.6-59U</b>	Ferrule, ( I.D. 6.6mm ), for RG59/U
<b>FER-6.9-8X</b>	Ferrule, ( I.D. 6.9mm ), for 8X (Mini 8/U)
<b>FER-5.6-58U</b>	Ferrule, ( I.D. 5.6mm ), for RG58/U
<b>FER-3.2-174U</b>	Ferrule, ( I.D. 3.2mm ), for RG174/U
<b>FER-8.0-6U</b>	Ferrule, ( I.D. 8.0mm ), for RG6/U
<b>FER-4.45-8218</b>	Ferrule, ( I.D. 4.45mm), for Belden 8218
<b>FER-8.5-8281</b>	Ferrule, ( I.D. 8.5mm), for Belden 8281
<b>FER-10.6-8U</b>	Ferrule, ( I.D. 10.6mm ), for RG8/U
<b>FER-10.7-L400</b>	Ferrule, ( I.D. 10.7mm ), ID for L400 Cable
<b>FER-10.9-214U</b>	Ferrule, ( I.D. 10.9mm ), for RG214U
<b>FER-T3044-179-U</b>	Step Ferrule, for RG179/U
<b>FER-T4756-58U</b>	Step Ferrule, for RG58/U Plenum Cable
<b>FER-T5466-59U</b>	Step Ferrule, for RG59 Plenum Cable

### All Captive Pin with 3 μ" Gold Plated

<b>BNC-P/M-0.5-179</b>	Male Pin ( Bore Dia. 0.50mm )
<b>BNC-P/M-0.6NC</b>	Male Pin Non-Captive( Bore Dia. 0.60mm )
<b>BNC-P/M-0.76</b>	Male Pin ( Bore Dia. 0.76mm )
<b>BNC-P/M-0.90</b>	Male Pin ( Bore Dia. 0.90mm )
<b>BNC-P/M-1.10</b>	Male Pin ( Bore Dia. 1.10mm )
<b>BNC-P/M-1.7-11</b>	Male Pin ( Bore Dia. 1.70mm ) For RG11
<b>BNC-P/F-0.76</b>	Female Pin ( Bore Dia. 0.76mm )
<b>BNC-P/F-0.90</b>	Female Pin ( Bore Dia. 0.90mm )
<b>BNC-P/F-1.10</b>	Female Pin ( Bore Dia. 1.10mm )

### All Captive Pin with 30 μ" Gold Plated

<b>BNC-PIN/M-0.76-30μ"</b>	Pin Hole ( Bore Dia. 0.76mm )
<b>BNC-PIN/M-0.90-30μ"</b>	Pin Hole ( Bore Dia. 0.90mm )
<b>BNC-PIN/M-1.10-30μ"</b>	Pin Hole ( Bore Dia. 1.10mm )

### Bushing & Washer

<b>BNC-RG62-BUSH</b>	Bushing for RG-62 Type Cable
<b>BNC-WSHR</b>	Washer, ID: 0.425"
<b>BNC-SLDRING</b>	RF/BNC Solder Ring Terminator



Plenum

Ferrule

BUSHING

0.14 in