


# DATA SWITCH BOXES & ACTIVE DEVICES



## MINI BREAK OUT BOXES (Data Switch Boxes)

- 12 Circuit Monitor LEDs
- Access To all RS232/V24, RS232/V.35, RS232/X21 Circuit
- Pocket Size, w/ Jumpers Included.

**MNI-BRKBOX** Mini breakout box for RS232/DB25

**MNI-MPS** Mini Monitor Power Saver

**BOB-V24** For V.24 interface, Rechargeable

**BOB-V35** For V.35 Interface

**BOB-X21** For X21 Interface



**MNI-MPS**



**BOB-X21**

## VGA MULTIPLIERS

- Sends out VGA output to as many as eight monitors
- Daisy Chainable up to 200 VGA Monitors
- Connects monitor up to 250 ft away
- Power Adapter Included
- Compatible to Multisync, SVGA, VGA, EGA, and CGA Monitor
- Maximum Resolution = 1024 x 1026
- Maximum Horizontal Frequency= 30 - 65 KHz
- Maximum Vertical Frequency= 43 - 90 Hz
- Maximum Video Band width 65 MHz (Min)

**VGA-L201**

**VGA-L401**

**VGA-L801**

**VGA-201**

**VGA-401**

**VGA-801**



## SIGNAL BOOSTERS

- No External Power or Battery is needed
- Boost Signal over 500 ft to extend the range of your parallel or Serial printer.

**ADL-SBP** Parallel Booster

**ADL-SBS** Serial Booster



**ADL-SBP**

## SIGNAL CONVERTERS

- Interchanges signals between Serial and Parallel Devices
- Bidirectional Converter or Uni-Directional Converter
- AC Adapter Included in some Converters

**ADL-S2P** Serial to Parallel Connector

**ADL-P2S** Parallel To Serial Connector

**ADL-PBIS** Bi-directional Connector Parallel to Serial

**ADL-PBIS-256** Single Converter, Bi-directional P/S



**ADL-PBIS-256**

## SHORT HAUL MODEM

- Duplex/Simplex Selectable
- DTE/DCE Selectable
- Up to 19Kbps under 0.8Km
- Up to 110 bps under 10Km
- Terminal Block or RJ-11 Jack for Wire Connection
- No External Adaptor Required

**ADL-SHMD**

