



FEATURES:

- Test clips with a right angle banana plug is ideal for use with hand held digital multimeter
- Extended slide on tip adapter fits directly over probe, allowing testing of hard to reach test points
- Probes, alligator clips and spade lugs fit directly onto test leads for test versatility
- Test accessories conveniently store in the tri-fold nylon pouch provided
- Compatible with most Fluke, H.P., Tektronix & Wavetek digital multimeters

MATERIALS:

Model **5907A**: Test Lead Straight to Right Angle: Banana Spring: Nickel plated beryllium copper, Insulation– Polypropylene, fire retardant, UL94 V-2, Wire: 48" silicone 18" AWG, Color: One Black, One Red,

RATINGS: 1000 VRMS, 10 Amperes

Model **5916A**: Medium Alligator Clip: Body–Steel, Nickel plated, Insulation– Polypropylene, fire retardant, UL94 V-2, Color: One Black, One Red, **RATINGS:** 300 VRMS, 5 Amperes

Model **6248**: Minigrabber to Banana Jack: Body: Nylon 6 – Fire Retardant – UL94 V-O Rated, Color per part number. Hook: Beryllium Copper, Gold Plated, Compression Spring: Music Wire. Wire: 18 AWG, 65 x 36 Tinned Copper, Insulation – Silicone, .144" (3,66 mm) O.D., Color per Part Number. Banana Jack: Body - Brass, Nickel Plated. Insulation - Nylon 6, Fire Retardant UL94 V-0 Rated, Color per part number. **RATINGS:** IEC 1010 2-031, Category III, P2 Compliant. Voltage: 600 VRMS/DC Max. Current: 5 Amperes Max.

Model **6261**: Minipincer to Banana Jack: Body: Nylon 6 – Fire Retardant – UL94 V-O Rated, Color per part number Pincer: Beryllium Copper, Gold Plated, Compression Spring: Music Wire. Wire: 18 AWG, 65 x 36 Tinned Copper, Insulation – Silicone, .144" (3,66 mm) O.D., Color per Part Number. Banana Jack: Body - Brass, Nickel Plated. Insulation - Nylon 6, Fire Retardant UL94 V-0 Rated, Color per part number. **RATINGS:** IEC 1010 2-031, Category III, P2 Compliant. Voltage: 600 VRMS/DC Max. Current: 5 Amperes Max.

Model **6252**: DMM Test Lead Coupler: Tubing: Brass, Nickel Plated, Insulation: Polypropylene, Color: One black and one red, **RATINGS:** IEC 1010, Operating Voltage: 1000 VRMS/DC, Current: 15 Amperes Max.

Model **5246**: IC Test Tip Adapter Insulation: Nylon. Tip: Stainless steel. Color: Black, Red, Green. **RATINGS:** +80°C. (+176°F.) Max.

Model **5689A**: Replaceable Tip Test Probe With Pop Jack, Body: Material: Nylon, POP JACK RECEPTACLE: Female Pop Jack (Compatible to 5547-48 Test Leads)

RATINGS: 600 VRMS, 10 Amperes

Model **6153**: Spade Lug w/ Jack **MATERIALS**: ETP 110 Copper, 1/2 Hard. Finish: Nickel Plated

Model **4174**: Stainless Steel Industrial Tip

Model **4988**: Stainless Steel Needle Tip

Model **5133**: Dog Leg Micro, Stainless Steel Tip

Model **5688**: Standard Probe Tip, nickel plated brass

Model **6242**: Micrograbber to Banana Plug

Model **6243**: SMD Grabber to Banana Plug

Model **5676**: Replaceable Tip DMM Test Probe Kit, Body: Nylon 6, Banana Plug: Insulator PVC, Banana Spring: Beryllium Copper, Plug: Nickel plated brass, Wire: 18 AWG, Silicon, **RATINGS**: Operating Voltage: 1000V, Current: 10 Amperes

Model **6041A**: Extra Large Alligator Clip: IEC -1010 Cat III P2, Jaws: Nickel Plated Steel, Insulation: Polyamide. **RATINGS**: Operating Temperature: -20° C to +80 C. Operating Voltage: 1000 VRMS. Current: 10 Amperes Max.

ORDERING INFORMATION: Model 5677A (Includes a kit of items from above)

Replacement P/N's: Model **5916A**: Medium Alligator Clip Set, Model **6153**: Spade Lug, Model **5907A**: Test Lead Straight to Right Angle Set, Model **6248-12-***: Grabber, Model **5246**: IC Test Tip Adapter Set, Model **6041A-***: Extra Large Alligator Clip: Model **5689A**: Replaceable Tip Test Probe with Pop Jack Set, Model **6153**: Spade Lug w/ Jack Model **4174**: Stainless Steel Industrial. Model **4988**: Stainless Steel Needle. Model **5133**: Dog Leg Micro, Stainless Steel. Model **5688**: Standard Probe tip nickel plated

* 0 = Black, 2 = Red. Model **6252**: DMM Coupler, Model **5676**: Replaceable Tip DMM Test Probe Kit. Model **6261**: Minipincer to Banana Jack, Model **6242**: Micrograbber to Banana Plug, Model **6243**: SMD Grabber to Banana Plug