


ET Series Tips for PES51 Soldering Pencil


The Weller Advantage

- The sensor hole in the base of the tip is fitted with a stainless steel liner to prevent the tip from seizing to the sensor




Screwdriver

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETA*	0.062	1.60	0.032	0.81	0.625	15.90
ETB*	0.093	2.40	0.020	0.51	0.625	15.90
ETC*	0.125	3.20	0.027	0.69	0.625	15.90
ETD	0.187	4.80	0.035	0.89	0.625	15.90
ETH	0.031	0.80	0.019	0.48	0.625	15.90




Long Screwdriver

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETJ	0.031	0.80	0.012	0.30	1.000	25.40
ETK*	0.046	1.20	0.026	0.66	1.000	25.40
ETL	0.078	2.00	0.027	0.69	1.000	25.40
ETM	0.125	3.20	0.037	0.94	1.000	25.40




Narrow Screwdriver

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETR	0.062	1.60	0.044	1.12	0.625	15.90




Conical

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETP*	0.031	0.80	0.012	0.30	0.625	15.90
ETT	0.024	0.60	0.036	0.91	0.625	15.90




Long Conical

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETO*	0.031	0.80	0.044	1.12	1.000	25.40
ETS*	0.015	0.40	--	--	1.000	25.40



Single Flat

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETAA	0.062	1.60	0.040	1.02	0.625	15.90
ETBB	0.093	2.40	0.032	0.81	0.625	15.90
ETCC	0.125	3.20	0.032	0.81	0.625	15.90
ETDD	0.187	4.80	0.032	0.81	0.625	15.90
ETU	0.015	0.40	--	--	0.700	17.80
ETV	0.024	0.60	--	--	0.700	17.80



Knife

Cat. No.	A		B		C	
	in.	mm	in.	mm	in.	mm
ETKN	0.180	4.57	0.064	1.63	0.625	15.90