Action-Electronics.com Order: 1-800-563-9405

EURO MAG TERMINAL BLOCKS

DePluggable Printed Circuit Mount Male Header Sockets

These sockets are available in both Vertical & Horizontal configurations and mate with the 13-2500 and 13-2600 series. They have closed side bases and a mating latch to prevent accidental disconnection of the plugs.

Specifications:
Rating: 15A @ 300V
UL Listed & CSA Certified
Center Spacing: .2" (5.08 mm)
Contact Material: Tin Plated Brass
Housing Material: Type 6/6 Polyamide 94VO
Recommended PC Hole size: .055" (1.40 mm)
use #55 drill bit Philmore # 12-552
Operating Temperature: 105°C (221°F) max.
-40°C (-40°F) min.



Horizontal

Vertical Mount

Part Number	# Positions	Length
13-2702	2	12.08 mm
13-2703	3	17.16 mm
13-2704	4	22.24 mm
13-2705	5	27.32 mm
13-2706	6	32.40 mm
13-2708	8	42.56 mm
13-2710	10	52.72 mm
13-2712	12	62.88 mm

Horizontal Mount

Part Number	# Positions	Length
13-2802	2	12.08 mm
13-2803	3	17.16 mm
13-2804	4	22.24 mm
13-2805	5	27.32 mm
13-2806	6	32.40 mm
13-2808	8	42.56 mm
13-2810	10	52.72 mm
13-2812	12	62.88 mm

EURO STYLE BARRIER STRIP

These Euro style barrier strips are available in several sizes depending on your carry current needs. They are cutable to almost any desired length. These terminal blocks are available in 20A, 30A, 35A, and 50A versions.

Description:
Base: With 1.2 - 2.5mm raised base
Housing Material: Polyamide 66 (Nylon 66), UL 94V-2
Temperature Rating: 105°C (UL), -30°C to 110°C (VDE)
Terminal Insert: Brass metal alloy, nickel plated
Screw: Zinc plated

Model	Clamping Area	Wire Range (Cu, AWG)	Screw	Dimensions (mm / inch)							
				Unit	A	B	C	D	E	F	
13-1208	2.5mm²	22-12 Sol/Str	M2.6x5	(mm)	96.20	17.00	14.50	8.00	2.90	2.8 ± 0.1	600V 20 AMP
				(inch)	3.79	0.67	0.57	0.32	0.11	0.11	
13-1210	4.0mm²	22-10 Sol 14-10 Str	M3.0x6	(mm)	117.5	20.20	17.00	10.00	3.60	3.4 ± 0.1	600V 30 AMP
				(inch)	4.63	0.80	0.67	0.39	0.14	0.13	
13-1216	6.0mm²	22-10 Sol/Str	M3.5x7	(mm)	140.7	23.80	19.00	12.00	3.90	4.2 ± 0.1	600V 35 AMP
				(inch)	5.40	0.94	0.75	0.47	0.15	0.15	
13-1232	10.0mm²	20-8 Sol/Str	M4.0x9	(mm)	158.0	25.60	25.20	13.50	4.40	5.0 ± 0.1	600V 50 AMP
				(inch)	6.22	1.01	0.99	0.53	0.17	0.19	



Action-Electronics.com Order: 1-800-563-9405